

SAFETY DATA SHEET X-433 AEROSOL

Supersedes Date: 04/24/2024

Issuing Date: 07/10/2025

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: X-433 AEROSOL
Recommended use Lubricant
Information on Manufacturer
CERTIFIED LABS, DIV. OF NCH CORP.
BOX 152170
IRVING, TEXAS 75015

Product Code: 5033
Chemical nature Aerosol
Emergency Telephone
CHEMTREC® 800-424-9300
Telephone inquiry
972-579-2477

2. HAZARD IDENTIFICATION

Color Gray
Appearance Opaque

Physical state Liquid

Odor Solvent

GHS
Classification
Physical Hazards
Aerosols

Category 2

Health Hazard
Reproductive toxicity
Specific target organ toxicity (repeated exposure)
Aspiration hazard

Category 2
Category 1
Category 1

Hazards not otherwise classified (HNOC)
Not applicable

Labeling
Signal word
Danger



Hazard statements
Flammable aerosol
Pressurized container: May burst if heated.
Suspected of damaging fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

Precautionary statements
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not breathe vapors or mists.
Do not eat, drink or smoke when using this product.
Wear protective gloves, protective clothing and eye protection.
Wash face, hands and any exposed skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms, call a physician.
IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.
IF exposed or concerned, get medical advice.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents and container in accordance with applicable regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	64742-52-5	15-40
Isobutane	75-28-5	3-7
Propane	74-98-6	3-7
Stoddard solvent	8052-41-3	3-7

Hexylene glycol	107-41-5	1-5
-----------------	----------	-----

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye contact	No hazards which require special first aid measures.
Skin contact	No hazards which require special first aid measures.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause redness and irritation.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Aspiration hazard if swallowed - can enter lungs and cause damage. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
---------------------------	--

5. FIRE-FIGHTING MEASURES

Flash Point 201.2 °F / 94 °C	Method Seta closed cup	
Flammability Limits in Air %: Mixture.	Upper flammability limit: 9.5	Lower flammability limit: 0.9
Suitable Extinguishing Media		
Foam. Carbon dioxide (CO2). Water spray. Dry powder. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Specific hazards arising from the chemical		
Flammable. Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: 9.8 inches / 25 cm and Burnback: 0 inch / 0 cm. Material can create slippery conditions.		
Protective Equipment and Precautions for Firefighters		
As in any fire, wear self-contained breathing apparatus pressure-demand, NOHSC (approved or equivalent) and full protective gear.		
Aerosol Level (NFPA 30B) -	3	
NFPA	Health hazards 2	Flammability 4
HMIS	Health hazards 2 *	Flammability 4
		Stability 0
		Physical Hazard 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Material can create slippery conditions.
Environmental precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.
Neutralizing Agent	Not applicable.

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin, eyes and clothing. Do not breathe vapors or mists.			
Storage	Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition.			
Storage Temperature	Minimum	35 °F / 2 °C	Maximum	120 °F / 49 °C
Storage Conditions	Indoor	X	Outdoor	Heated
				Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical name	CAL/OSHA PEL	ACGIH TLV	OSHA PEL	NIOSH
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	No data available	TWA: 5 mg/m ³ ; STEL: 10 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³ ; STEL: 10 mg/m ³ ; IDLH: 2500 mg/m ³
Isobutane	No data available	STEL: 1000 ppm explosion hazard	No information available	TWA: 800 ppm; TWA: 1900 mg/m ³ ;
Propane	1000 ppm	Simple Asphyxiant. Significant quantities of component may displace oxygen, which is the limiting factor for exposure. See Appendix F of ACGIH Threshold Limit Values for Chemical Substances and Physical Agents for more information.	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	TWA: 1000 ppm; TWA: 1800 mg/m ³ ; STEL: 1250 ppm; STEL: 2250 mg/m ³ ; IDLH: 2100 ppm; IDLH: 3400 ppm
Stoddard solvent	100 ppm	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	TWA: 350 mg/m ³ ; Ceiling: 1800 mg/m ³ 15 min; IDLH: 20000 mg/m ³
Hexylene glycol	25 ppm	TWA: 25 ppm vapor fraction STEL: 50 ppm vapor fraction STEL: 10 mg/m ³ inhalable particulate matter, aerosol only	(vacated) Ceiling: 25 ppm (vacated) Ceiling: 125 mg/m ³	Ceiling: 25 ppm Ceiling: 125 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment**Eye/Face Protection**

Safety glasses with side-shields.

Skin Protection

For prolonged or repeated contact, use protective gloves with appropriate chemical resistance.

Respiratory Protection

In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations

Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use. Wear protective gloves/clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Kinematic viscosity	Slightly viscous
Color	Gray	Odor	Solvent
Odor threshold	Not applicable	Appearance	Opaque
pH	Not applicable	Specific Gravity	0.857
Evaporation Rate	18.85 (Butyl acetate=1)	Percent Volatile (Volume)	No data available
VOC content	10.22	VOC Content (g/L)	87.62
Product VP (mmHg @ 70°F)	1778.93	Relative vapor density	1.4 (air = 1)
Solubility(ies)	Negligible	n-Octanol/Water Partition	No data available
Melting Point/Range	No data available	Decomposition temperature	No data available
Initial boiling point and boiling range	No data available	Flammability (solid, gas)	No data available
Flash Point	201.2 °F / 94 °C	Method	Seta closed cup
Autoignition Temperature	No information available	Upper flammability limit: 9.5 Lower flammability limit: 0.9	
Flammability Limits in Air %:	Mixture		

10. STABILITY AND REACTIVITY

Chemical Stability
Conditions to Avoid

Stable. Hazardous polymerization does not occur.
Keep away from open flames, hot surfaces, and sources of ignition. Extremes of temperature and direct sunlight.

Incompatible Products**Decomposition temperature****Hazardous decomposition products**

Strong oxidizing agents, Strong acids, Aldehydes, Ketones.
No data available
Carbon oxides, Nitrogen oxides (NOx), Sulfur oxides, Aldehydes, Ketones.

Possibility of Hazardous Reactions

None under normal processing.

11. TOXICOLOGICAL INFORMATION

Product Information

No information available

The following ATE values have been calculated for the mixture**ATEmix (oral)**

No information available

ATEmix (dermal)

No information available

Inhalation LC50**ATEmix (inhalation-gas)**

No information available

ATEmix (inhalation-dust/mist)

No information available

ATEmix (inhalation-vapor)

No information available

Principle Route of Exposure

Inhalation, Skin contact, Eye contact, Ingestion.

Primary Routes of Entry

Inhalation, Eye contact, Skin contact, Ingestion.

Acute Effects:**Eyes**

Low hazard for usual industrial or commercial handling.

Skin
Inhalation
Ingestion

Low hazard for usual industrial or commercial handling.
Low hazard for usual industrial or commercial handling.
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes headache, drowsiness or other effects to the central nervous system. Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.
Causes damage to organs through prolonged or repeated exposure. Contains a known or suspected reproductive toxin.
Central nervous system, Respiratory system, Eyes, Skin.
Respiratory disorders, Neurological disorders, Skin disorders.

Chronic toxicity

Target organ effects

Aggravated Medical Conditions

Component Information

Acute Toxicity

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Others
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable) 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	= 2062 ppm (Rat) 4 h	No data available	No data available
Isobutane 75-28-5	No data available	No information available	= 658 mg/L (Rat) 4 h	No data available	No data available
Propane 74-98-6	No data available	No information available	658 mg/L (Rat) 4h	No data available	No data available
Stoddard solvent 8052-41-3	No data available	> 3000 mg/kg (Rabbit)	> 5.5 mg/L (Rat) 4 h	No data available	No data available
Hexylene glycol 107-41-5	= 3700 mg/kg (Rat)	= 12300 mg/kg (Rabbit)	> 310 mg/m ³ (Rat) 1 h	No data available	No data available

Chronic Toxicity

Chemical name	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable) 64742-52-5	No data available	No data available	No data available	No data available	Skin Eyes Respiratory system
Isobutane 75-28-5	No data available	No data available	No data available	No data available	Central Nervous System
Propane 74-98-6	No data available	No data available	No data available	No data available	Central Nervous System Respiratory system
Stoddard solvent 8052-41-3	No data available	No data available	No data available	No data available	Skin Central Nervous System Eyes Respiratory system Kidney
Hexylene glycol 107-41-5	No data available	No data available	No data available	X	Skin Central Nervous System Eyes Respiratory system

Carcinogenicity

There are no known carcinogens in this product.

12. ECOLOGICAL INFORMATION

Product Information No information available

Persistence and Degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Additional Ecological Information: No information available

Component Information

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to microorganisms	Crustacea	Partition coefficient
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	No information available	LC50 > 5000 mg/L Oncorhynchus mykiss 96 h	No information available	EC50: >1000mg/L (48h, Daphnia magna)	-
Isobutane	No information available	No information available	No information available	No information available	2.8
Propane	No information available	No information available	No information available	No information available	2.8
Stoddard solvent	No information available	No information available	No information available	No information available	6.4
Hexylene glycol	No information available	LC50 10500 - 11000 mg/L Pimephales promelas 96 h LC50 = 10000 mg/L Lepomis macrochirus 96 h LC50 = 8690 mg/L Pimephales promelas 96 h LC50 = 10700 mg/L Pimephales promelas 96 h	EC50 = 3038 mg/L 5 min	EC50: 2700 - 3700mg/L (48h, Daphnia magna)	0.13986

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal	Dispose of in accordance with local regulations.
Container Disposal	Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT	
Proper shipping name	AEROSOLS, FLAMMABLE
Transport hazard class(es)	2.1
UN number or ID number	UN1950
Description	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY
TDG	
UN proper shipping name	AEROSOLS, FLAMMABLE
Transport hazard class(es)	2.1
UN number or ID number	UN1950
Description	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY
ICAO (air)	
UN number or ID number	UN1950
UN proper shipping name	AEROSOLS, FLAMMABLE
Transport hazard class(es)	2.1
Description	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY
IATA	
UN number or ID number	UN1950
UN proper shipping name	AEROSOLS, FLAMMABLE
Transport hazard class(es)	2.1
ERG-Code	10L
Description	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY
IMDG	
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
UN number or ID number	UN1950
EmS-No	F-D, S-U
Description	UN1950, AEROSOLS, 2.1, LTD QTY

15. REGULATORY INFORMATION

Inventories	
TSCA	Listed
DSL/NDL	Listed
US Federal Regulations	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

16. OTHER INFORMATION

Prepared By	Hazard Communication Department
Supersedes Date:	04/24/2024
Issuing Date:	07/10/2025
Revision Note	No information available
Glossary	No information available
List of References.	No information available

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.